

DIGITAL MULTIMETER MS8360C / MS8360E

EMC
LVD



MS8360E

VOLTAGE AC 600V
DC 600V

CURRENT AC 10A
DC 10A



Specifications

MS8360C MS8360E

Specifications	Range	Accuracy	
DC Voltage	200mV/2V/20V/200V	±(0.5%+1)	±(0.5%+1)
	600V	±(0.8%+2)	±(0.8%+2)
AC Voltage	2V/20V/200V	±(0.8%+3)	±(0.8%+3)
	600V	±(1.2%+3)	±(1.2%+3)
DC Current	20mA	±(0.8%+1)	
	200mA	±(1.5%+1)	±(1.5%+1)
AC Current	10A	±(2.0%+5)	±(2.0%+5)
	20mA	±(1.0%+3)	
AC Current	200mA	±(1.8%+3)	±(1.8%+3)
	10A	±(3.0%+7)	±(3.0%+7)
Resistance	200Ω	±(0.8%+3)	±(0.8%+3)
	2KΩ/20KΩ/200KΩ/2MΩ	±(0.8%+1)	±(0.8%+1)
	20MΩ	±(1.0%+2)	±(1.0%+2)
Capacitance	200nF/200nF/2μF/20μF	±(5.0%+10)	±(5.0%+10)
	200μF	±(5.0%+10)	±(5.0%+10)
Frequency	20KHz	±(1.5%+5)	
Temperature	-20°C~0°C	±(5.0%+4)	
	1°C~400°C	±(2.0%+3)	
	401°C~1000°C	±(2.0%+5)	
Inductance	20mH/200mH/2H/20H		±(3.0%+5)

Features

Features	MS8360C	MS8360E	
Display	counts	2000	2000
APO	Auto Power Off	●	●
NCV	Non-Contact Voltage Detector	●	●
Transistor hFE	0~1000	●	●
Diode	2.7V	●	●
Continuity Buzzer	≤30Ω	●	●
Data Hold		●	●
Display Backlight		●	●
LBD	Low Battery Display	●	●

General

Power Supply	1×9V6F22 Battery
Product Size	188mm×92mm×50mm/7.4"×3.6"×2.0"
Product Weight	380g/0.83lb
Safety Rating	CE ETL CAT III 600V RoHS

● Feature Difference